



JOHN DEERE



DESCRIPTIVE

- Mechanical governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for wiring temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1.

Overload is not allowed

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

JD200M

John Deere Engine type	6068HF258
Meccalte Alternator type	ECO38-1S4A
Performance class	G3

GENERAL CHARACTERISTICS

Frequency (Hz)	50
Reference voltage (V)	400/230
Max power ESP (kVA)	200
Max power ESP (kWe)	160
Max power PRP (kVA)	180
Max power PRP (kWe)	144
Intensity (A)	289
Standard Control Panel	DSE 4510
Optional control panel	DSE 6610

DIMENSIONS COMPACT VERSION

Length (mm)	2500
Width (mm)	1000
Height (mm)	1361
Dry weight (kg)	1726
Tank capacity (L)	340

GENERAL CHARACTERISTICS

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
415/240	160	200	144	180	278
400/230	160	200	144	180	289
380/220	160	200	144	180	304
240 TRI	160	200	144	180	481
230 TRI	160	200	144	180	502
220 TRI	160	200	144	180	525
200/115	160	200	144	180	577



JOHN DEERE



JD200M

ENGINE SPECIFICATIONS

GENERAL ENGINE DATAS

Engine model	JOHN DEERE 6068HF258 , 4- temps, Turbo , Air/Air DC 6 X
Cylinder arrangement	L
Displacement (C.I.)	6.72
Bore (mm) x Stroke (mm)	106 x 127
Compression ratio	17 : 1
Speed (RPM)	1500
Pistons speed (m/s)	6.35
Maximum stand-by power at rated RPM (kW)	183
Frequency regulation (%)	+/- 2.5%
BMEP (bar)	19.80
Governor type	Mechanical

COOLING SYSTEM

Radiator & Engine capacity (L)	26
Max water temperature (°C)	105
Outlet water temperature (°C)	93
Fan power (kW)	3.4
Fan air flow w/o restriction (m3/s)	4.6
Available restriction on air flow (mm EC)	20
Type of coolant	Cool Guard
Thermostat (°C)	82-94

EMISSIONS

Emission PM (mg/Nm3) 5% O2	80
Emission CO (mg/Nm3) 5% O2	180
Emission HC+NOx (g/kWh)	0
Emission HC (g/kW.h)	

EXHAUST

Exhaust gas temperature (°C)	565
Exhaust gas flow (L/s)	457
Max. exhaust back pressure (mm EC)	750

FUEL

Consumption @ 110% load (L/h)	45.2
Consumption @ 100% load (L/h)	40.8
Consumption @ 75% load (L/h)	31.30
Consumption @ 50% load (L/h)	20.5
Maximum fuel pump flow (L/h)	108

OIL

Oil capacity (L)	32
Min. oil pressure (bar)	1
Max. oil pressure (bar)	5
Oil consumption 100% load (L/h)	0.04
Carter oil capacity (L)	31.5

HEAT BALANCE

Heat rejection to exhaust (kW)	138
Radiated heat to ambient (kW)	23
Haet rejection to coolant (kW)	76

AIR INTAKE

Max. intake restriction (mm EC)	625
Intake air flow (L/s)	205



JD200M

ALTERNATOR SPECIFICATIONS

GENERAL DATAS

Alternator brand	Meccalte
Alternator type	ECO38-1S4A
Number of phase	3
Power factor (Cos Phi)	0.8
Altitude (m)	0 to 1000
Overspeed (rpm)	2250
Number of pole	4
Excitation system	SHUNT
Insulation class / T° class, continuous 40°C	H / H / 125°K
Regulation	DSR
Harmonic factor, no load TGH/THC	<2.5
Wave form : NEMA=TIF-(TGH/THC)	<50
Wave form : CEI=FHT-(TGH/THC)	<20
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (%)	+/- 0.5%
Recovery time (Delta U = 20% transient) (ms)	500

OTHER DATAS

Continuous Nominal Rating 40°C (kVA)	180
Standby Rating 27°C (kVA)	196
Efficiencies 4/4 load (%)	93.2
Air flow (m3/s)	0.321
Short circuit ratio (Kcc)	0.44
Direct axis synchro reactance unsaturated (Xd) (%)	203.9
Quadra axis synchro reactance unsaturated (Xq) (%)	83.2
Open circuit time constant (T'do) (sec)	0.7
Direct axis transient reactance saturated (X'd) (%)	8.33
Short circuit transient time constant (T'd) (sec)	0.073
Direct axis subtransient reactance saturated (X''d) (%)	4.72
Subtransient time constant (T''d) (sec)	0.011
Quadra axis subtransient reactance saturated (X''q) (%)	16.9
Zero sequence reactance unsaturated (Xo) (%)	2.79
Negative sequence reactance saturated (X2) (%)	11
Armature time constant (Ta) (sec)	0.015
No load excitation current (io) (A)	0.7
Full load excitation current (ic) (A)	301
Full load excitation voltage (uc) (V)	40.90
Recovery time (Delta U = 20% transient) (ms)	500
Engine start (Delta U = 20% perm. or 50% trans.) (kVA)	407.60
Transient dip (4/4 load) - PF : 0,8 AR (%)	14
Heat rejection (W)	11844



JOHN DEERE



JD200M

CONTROL PANEL

DSE Deep Sea Electronics 4610 Standard

DSE Deep Sea Electronics 6010 optional

The DSE 4610 MRS is a versatile unit which can be operated in manual or automatic mode. It offers the following features:

Measurements:

phase-to-neutral and phase-to-phase voltages,
(In option: active power currents, effective power, power factor, oil pressure and coolant temperature levels)

Supervision:

Modbus RTU communication on RS485

Reports:

(In option: 2 configurable reports)

Safety features:

Over speed, oil pressure, coolant temperatures, minimum and maximum voltage, minimum and maximum frequency

(Maximum active power $P < 66\text{kVA}$)

Traceability:

Stack of 50 stored events

For further information, please refer to the data sheet for the DSE 4610.

The DSE 6010 MRS is a versatile control unit which allows

operation in manual or automatic mode

Measurements:

voltage and current, kW/kWh/kVA power meters
Standard specifications: Voltmeter, Frequency meter.
Optional: Battery ammeter.

J1939 CAN ECU engine control

Alarms and faults: Oil pressure, Coolant temperature, Over speed, Start-up failure, alternator min/max, Emergency stop button.

Engine parameters: hour counter, battery voltage.

Optional (standard at 12V): Oil pressure, water temperature.

Event log/ Management of the last 50 gen set events.

Mains and gen set protection

Clock management

USB connections, USB Host and PC,

Communications: RS485 INTERFACE

Mod BUS protocol /SNMP

Optional: Ethernet, GPRS, remote control, 3G, 4G, Web supervisor, SMS, E-mails